

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

1422A TYVEK® AUTOCLAVE BAG WITH STEAM INDICATOR



TYPICAL APPLICATION & CHARACTERISTICS:

Recommended for Steam Sterilization of Pharmaceutical Production Equipment

- Cost Effective
- Tyvek® on both sides for maximum steam penetration during sterilization
- Minimizes the use of autoclave tape
- Fast and consistent for equipment preparation area
- Creates strong seals when heat sealed
- Hydrophobic
- Resists tearing and punctures
- Superior microbial barrier
- Lint-Free
- Manufactured and packaged in ISO certified cleanrooms
- Certificates of Conformance sent with all shipments
- Made in USA

MATERIAL SPECIFICATIONS:

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®
Seal Strength	N/mm	F-88	>.78
Basis Weight	g/m2	EN ISO 536	41
Total Thickness	μ	EN 20534	130
Air Permeability	s	ISO 5636-5	20
Water Vapor Permeability	G/M2/24 HR	ASTM 398	1700
Hydrostatic Head	cm h2o	ISO 811	120
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent
Burst Resistance	kPa	ISO 2960 (50 cm2)	108
Puncture Resistance	N	EN 863	10.8
Melting Point	c°		135

SINCE 1925

KEYSTONE

SAFETY ↔ CLEANROOM PRODUCTS

1422A TYVEK® AUTOCLAVE BAG WITH STEAM INDICATOR



KEYSTONE PART NUMBER	DIMENSIONS	KEYSTONE PART NUMBER	DIMENSIONS
BGT2A0205	2" x 5"	BGT2A1624	16" X 24"
BGT2A0404	4" X 4"	BGT2A1830	18" X 30"
BGT2A0409	4" x 9"	BGT2A2020	20" X 20"
BGT2A0416	4" x 16"	BGT2A2024	20" x 24"
BGT2A0820	8" x 20"	BGT2A2030	20" x 30"
BGT2A09-512	9.5" x 12"	BGT2A2040	20" x 40"
BGT2A1015	10" x 15"	BGT2A2224	22" x 24"
BGT2A1020	10" X 20"	BGT2A2424	24" x 24"
BGT2A1212	12" x 12"	BGT2A2436	24" x 36"
BGT2A1216	12" x 16"	BGT2A2448	24" x 48"
BGT2A1218	12" x 18"	BGT2A2844	28" x 44"
BGT2A1234	12" x 34"	BGT2A3036	30" X 36"
BGT2A1240	12" x 40"	BGT2A3636	36" x 36"
BGT2A1246	12" x 46"	BGT2A3648	36" X 48"
BGT2A1248	12" x 48"	BGT2A3660	36" x 60"
BGT2A1424	14" x 24"	BGT2A4848	48" x 48"