

SINCE 1925

KEYSTONE

SAFETY ⇄ CLEANROOM PRODUCTS

1422A TYVEK® STEAM STERILIZATION WRAPPER



MATERIAL SPECIFICATIONS:

TYPICAL APPLICATION & CHARACTERISTICS:

- Designed for steam sterilization
- Recommended for use in conjunction with a secondary Tyvek® sterilization pouch
- Hydrophobic
- Excellent Microbial Barrier
- Resists tearing and punctures
- Lint-free
- Manufactured and packaged in ISO certified cleanrooms
- Certificates of Conformance sent with all shipments
- Made in USA

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®
Basis Weight	g/m2	EN ISO 536	41
Total Thickness	μ	EN 20534	130
Air Permeability	s	ISO 5636-5	20
Water Vapor Permeability	G/M2/24 HR	ASTM 398	1700
Hydrostatic Head	cm h20	ISO 811	120
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent
Burst Resistance	kPa	ISO 2960 (50 cm2)	108
Puncture Resistance	N	En 863	10.8
Melting Point	C°		135

SINCE 1925

KEYSTONE

SAFETY ⇄ CLEANROOM PRODUCTS

1422A TYVEK® STEAM STERILIZATION WRAPPER



KEYSTONE PART NUMBER	DIMENSIONS	KEYSTONE PART NUMBER	DIMENSIONS
T2ASHEET0303	3" X 3"	T2ASHEET2020	20" X 20"
T2ASHEET0404	4" X 4"	T2ASHEET2424	24" X 24"
T2ASHEET0606	6" X 6"	T2ASHEET3030	30" X 30"
T2ASHEET07-507-5	7.5" X 7.5"	T2ASHEET4040	40" X 40"
T2ASHEET0909	9" X 9"	T2ASHEET4080	40" X 80"
T2ASHEET0911	9" X 11"	T2ASHEET6060	60" X 60"
T2ASHEET1212	12" X 12"	T2ASHEET60140	60" X 140"
T2ASHEET1515	15" X 15"	T2ASHEET7272	72" X 72"
T2ASHEET1818	18" X 18"	T2ASHEET8494	84" X 94"