

SELF-SEALING 1422A TYVEK® AUTOCLAVE BAG WITH STEAM INDICATOR



TYPICAL APPLICATION & CHARACTERISTICS:

- Eliminate the need for autoclave tape
- Eliminate the need for heat sealer validation
- Recommended for steam sterilization of pharmaceutical production equipment
- Cost-effective
- Tyvek® on both sides for maximum penetration during sterilization
- Fast and consistent for equipment preparation area
- Hydrophobic
- Resists tearing and punctures
- Superior microbial barrier
- Lint-Free
- Manufactured and packaged in ISO certified Cleanroom
- Certificates of Conformance sent with all shipments
- Made in USA

MATERIAL SPECIFICATIONS:

PROPERTY	UNITS	TEST METHOD	TYPICAL VALUES 1422A TYVEK®	
Seal Strength	N/mm	F-88	>.78	
Basis Weight	g/m2	EN ISO 536	41	
Total Thickness	μ	EN 20534	130	
Air Permeability	s	ISO 5636-5	20	
Water Vapor Permeability	G/M2/24 HR	ASTM 398	1700	
Hydrostatic Head	cm h2o	ISO 811	120	
Trapezoidal Tear MD/CD	N	ISO 9073-4	26.1/30.6	
Linting Propensity	Rating	BS 6909 (Shirley Method 21)	Pass Rating: Excellent	
Burst Resistance	kPa	ISO 2960 (50 cm2)	108	
Puncture Resistance	N	EN 863	10.8	
Melting Point	c°		135	



SELF-SEALING 1422A TYVEK® AUTOCLAVE BAG WITH STEAM INDICATOR







KEYSTONE PART NUMBER	DIMENSIONS	KEYSTONE PART NUMBER	DIMENSIONS
BGT2A0205SS	2" x 5"	BGT2A1830SS	18" X 30"
BGT2A0404SS	4" X 4"	BGT2A2020SS	20" X 20"
BGT2A0409SS	4" x 9"	BGT2A2024SS	20" x 24"
BGT2A0416SS	4" x 16"	BGT2A2030SS	20" x 30"
BGT2A0820SS	8" x 20"	BGT2A2040SS	20" x 40"
BGT2A09-512SS	9.5" x 12"	BGT2A2224SS	22" x 24"
BGT2A1015SS	10" x 15"	BGT2A2424SS	24" x 24"
BGT2A1020SS	10" X 20"	BGT2A2436SS	24" x 36"
BGT2A1212SS	12" x 12"	BGT2A2448SS	24" x 48"
BGT2A1216SS	12" x 16"	BGT2A2844SS	28" x 44"
BGT2A1218SS	12" x 18"	BGT2A3036SS	30" X 36"
BGT2A1234SS	12" x 34"	BGT2A3636SS	36" x 36"
BGT2A1240SS	12" x 40"	BGT2A3648SS	36" X 48"
BGT2A1246SS	12" x 46"	BGT2A3660SS	36" x 60"
BGT2A1248SS	12" x 48"	BGT2A4848SS	48" x 48"
BGT2A1624SS	16" x 24"		

